

MAER

HIGH PRESSURE CLEANERS



AVANT

HIGH PRESSURE CLEANERS
NETTOYEURS HAUTE PRESSION
IDROPULITRICI ALTA PRESSIONE
LIMPIADORAS ALTA PRESION
HOCHDRUCKREINIGER

MAER

IDROPULITRICI

Technical features/Caractéristiques techniques/Caratteristiche tecniche/Características técnicas/Technische Eigenschaften

MODEL MODELE MODELLO MODELO MODEL	PRESSURE PRESSION PRESSIONE PRESION DRUCK	WATER DELIVERY DEBIT PORTATA CAUDAL WASSERMENGE	TEMPERATURE TEMPERATURE TEMPERATURA TEMPERATURA TEMPERATUR	MOTOR POWER PUISSANCE MOTEUR POTENZA MOTORE POTENCIA MOTOR MOTOR LEISTUNG	POWER SUPPLY ALIMENTATION ALIMENTAZIONE ALIMENTACION SPANNUNG	ABS. POWER PUISSANCE ABS. POTENZA ASS. POTENCIA ABS. AUF. LEISTUNG	DIMENSIONS DIMENSIONS DIMENSIONI DIMENSIONES ABMESSUNGEN	WEIGHT POIDS PESO PESO GEWICHT
	bar psi	lt/h gal/h	°C	hp kw rpm		kw	cm	kg
AVANT 12/10	120-1750	600-158	0°-140°	3 2,2 1450	230V 50Hz MONO	2,5	100x63x85	125
AVANT 15/15	150-2175	900-237	0°-140°	5,5 4,0 1450	230/400V 50Hz TRI	4,4	100x63x85	140
AVANT 15/21	150-2175	1260-332	0°-140°	7,5 5,5 1450	230/400V 50Hz TRI	5,8	100x63x85	150
AVANT 20/15	200-2900	900-237	0°-140°	7,5 5,5 1450	230/400V 50Hz TRI	5,8	100x63x85	150
AVANT 20/21	200-2900	1260-332	0°-140°	10 7,3 1450	230/400V 50Hz TRI	7,8	100x63x85	170

Via Torre, 43/2 - Torre Pallavicina 24050 (Bergamo) - Italy - Tel. ++39 0363.996579 Fax ++39 0363.996688 www.maeridropulitrici.com



Technical features/Caractéristiques techniques/Caratteristiche tecniche/Características técnicas/Technische Eigenschaften

MODEL MODELE MODELLO MODELO MODEL	PRESSURE PRESSION PRESSIONE PRESION DRUCK	WATER DELIVERY DEBIT PORTATA CAUDAL WASSERMENGE	TEMPERATURE TEMPERATURE TEMPERATURA TEMPERATURA TEMPERATUR	MOTOR POWER PUISSANCE MOTEUR POTENZA MOTORE POTENCIA MOTOR MOTOR LEISTUNG	POWER SUPPLY ALIMENTATION ALIMENTAZIONE ALIMENTACION SPANNUNG	ABS. POWER PUISSANCE ABS. POTENZA ASS. POTENCIA ABS. AUF. LEISTUNG	DIMENSIONS DIMENSIONS DIMENSIONI DIMENSIONES ABMESSUNGEN	WEIGHT POIDS PESO PESO GEWICHT
▼	bar psi	lt/h gal/h	°C	hp kw rpm		kw	cm	kg
AVANT 12/10	120-1750	600-158	0°-140°	3 2,2 1450	230V 50Hz MONO	2,5	100x63x85	125
AVANT 15/15	150-2175	900-237	0°-140°	5,5 4,0 1450	230/400V 50Hz TRI	4,4	100x63x85	140
AVANT 15/21	150-2175	1260-332	0°-140°	7,5 5,5 1450	230/400V 50Hz TRI	5,8	100x63x85	150
AVANT 20/15	200-2900	900-237	0°-140°	7,5 5,5 1450	230/400V 50Hz TRI	5,8	100x63x85	150
AVANT 20/21	200-2900	1260-332	0°-140°	10 7,3 1450	230/400V 50Hz TRI	7,8	100x63x85	170

